

La Libertad Drilling Composites – September 8th, 2021

Drill Hole ID	Vein Structure	From (m)	To (m)	Interval (m)	ETW* (m)	Au (g/t)	Ag (g/t)
TR-21-048	Tranca <i>includes</i>	0.0	15.8	15.8		NS	NS
		15.8	33.1	17.4		0.03	0.1
		33.1	34.1	1.0	0.6	4.84	2.1
		34.1	63.2	29.2		0.02	0.5
		63.2	68.4	5.2		0.18	1.0
		68.4	76.1	7.7	4.5	1.73	3.1
		68.4	70.4	2.0		2.35	2.0
		70.4	72.4	2.0		0.63	4.5
		72.4	76.1	3.7		2.00	3.0
		76.1	94.1	18.0		0.08	0.4
94.1	109.7	15.6		NS	NS		
TR-21-051	Tranca	0.0	47.8	47.8		NS	NS
		47.8	60.4	12.6		0.07	0.7
		60.4	61.4	1.0	0.7	1.33	1.4
		61.4	75.7	14.3		0.11	0.8
		75.7	76.7	1.0	0.7	1.25	5.8
		76.7	91.1	14.5		0.09	0.5
		91.1	99.1	8.0		NS	NS
TR-21-053	Tranca	0.0	44.2	44.2		NS	NS
		44.2	86.6	42.4		0.03	0.4
		86.6	91.4	4.9	3.2	0.57	2.6
		91.4	99.4	8.0		0.08	1.1
		99.4	120.4	21.0		NS	NS
TR-21-054	Tranca <i>includes</i>	0.0	32.5	32.5		NS	NS
		32.5	39.8	7.3		0.02	0.6
		39.8	44.5	4.7	3.9	0.35	0.6
		44.5	52.7	8.2		NS	NS
		52.7	66.7	14.0		0.10	0.3
		66.7	67.5	0.8	0.6	0.85	1.4
		67.5	77.0	9.5		0.12	0.4
		77.0	87.0	10.0	7.6	3.34	8.3
		77.0	79.0	2.0		0.95	13.9
		79.0	83.0	4.0		4.57	9.3
		83.0	85.0	2.0		0.59	1.8
85.0	87.0	2.0		6.00	7.0		
87.0	90.7	3.7		0.26	0.9		
90.7	111.3	20.6		NS	NS		
TR-21-055	Tranca <i>includes</i>	0.0	49.2	49.2		NS	NS
		49.2	57.8	8.7		0.01	0.1
		57.8	91.5	33.7	22.3	1.71	5.8
		57.8	60.8	3.0		2.24	5.9
		60.8	67.8	7.0		0.53	0.9
		67.8	69.8	2.0		3.23	14.5
		69.8	72.8	3.0		1.01	2.2
		72.8	74.8	2.0		3.37	1.2
		74.8	82.8	8.0		1.06	1.4
		82.8	83.8	1.0		11.70	1.1
		83.8	85.8	2.0		0.73	2.2
		85.8	89.3	3.5		2.16	24.3
		89.3	91.5	2.2		0.84	14.1
		91.5	95.0	3.5		0.04	0.2
95.0	105.2	10.1		NS	NS		

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

Drill Hole ID	Vein Structure	From (m)	To (m)	Interval (m)	ETW* (m)	Au (g/t)	Ag (g/t)
TR-21-056	Tranca	0.0	74.8	74.8	1.7	NS	NS
		74.8	82.8	8.0		0.01	0.3
		82.8	84.8	2.0		0.99	2.2
		84.8	86.8	2.0		0.65	4.2
		86.8	94.0	7.3		0.08	0.6
		94.0	105.2	11.2		NS	NS
TR-21-057	Tranca	0.0	75.6	75.6	2.7	NS	NS
		75.6	90.3	14.8		0.02	0.5
		90.3	93.4	3.1		2.26	2.7
		93.4	97.4	4.0		0.01	0.2
		97.4	109.7	12.3		NS	NS
TR-21-058	Tranca	0.0	29.2	29.2		NS	NS
		29.2	48.8	19.6		0.00	0.2
TR-21-059	Tranca	0.0	28.0	28.0	3.3	NS	NS
		28.0	43.6	15.6		0.02	0.9
		43.6	47.6	4.0		1.29	2.5
		47.6	65.5	18.0		0.07	0.8
TR-21-060	Tranca	0.0	15.2	15.2		NS	NS
		15.2	34.0	18.8		0.03	0.6
		34.0	61.4	27.4		NS	NS
		61.4	81.0	19.6		0.01	0.3
		81.0	96.0	15.0		NS	NS
TR-21-061	Tranca	0.0	21.3	21.3	1.3	NS	NS
		21.3	22.3	0.9		0.06	2.2
		22.3	23.9	1.7		1.40	4.8
		23.9	24.9	1.0		0.05	0.7
		24.9	75.2	50.3	2.3	NS	NS
		75.2	84.4	9.2		0.03	0.5
		84.4	87.4	3.0		0.61	1.5
		87.4	92.8	5.4		0.10	0.8
92.8	109.7	16.9	NS	NS			
TR-21-062	Tranca <i>includes</i>	0.0	90.8	90.8	9.9	NS	NS
		90.8	96.0	5.3		0.10	1.6
		96.0	108.4	12.4		1.21	2.0
		96.0	100.7	4.6		2.29	3.2
		100.7	103.7	3.0		0.29	2.1
		103.7	104.4	0.8		2.15	2.2
		104.4	106.9	2.5		0.03	0.4
		106.9	108.4	1.5		1.17	0.6
108.4	113.9	5.5	NS	NS			
TR-21-063	Tranca	0.0	46.3	46.3	0.7	0.02	0.2
		46.3	63.0	16.8		NS	NS
		63.0	74.1	11.1		0.07	0.5
		74.1	75.1	1.0		1.45	3.7
		75.1	82.1	6.9		0.16	1.5
		82.1	105.2	23.1		NS	NS
TR-21-064	Tranca	0.0	18.3	18.3	1.4	NS	NS
		18.3	21.3	3.1		0.06	4.6
		21.3	22.9	1.5		1.53	24.8
		22.9	65.5	42.7		0.00	0.0
		65.5	97.9	32.3	0.8	0.03	0.3
		97.9	101.4	3.5		0.46	1.8
		101.4	102.4	1.0		1.98	2.4
		102.4	115.8	13.4		0.06	0.7

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

Drill Hole ID	Vein Structure	From (m)	To (m)	Interval (m)	ETW* (m)	Au (g/t)	Ag (g/t)
TR-21-065	Tranca	0.0	108.9	108.9	2.4	NS	NS
		108.9	112.4	3.5		0.00	0.4
		112.4	116.4	4.0		2.01	2.6
		116.4	121.2	4.8		0.03	0.6
		121.2	135.6	14.4		NS	NS
TR-21-066	Tranca <i>includes</i>	0.0	54.4	54.4	6.8	NS	NS
		54.4	59.4	5.1		0.03	0.3
		59.4	68.6	9.1		2.81	3.9
		59.4	63.4	4.0		2.11	3.4
		63.4	65.8	2.4		5.53	5.3
		65.8	68.6	2.8		1.50	3.6
TR-21-067	Tranca	0.0	81.9	81.9	2.4	NS	NS
		81.9	88.9	7.0		0.08	0.9
		88.9	91.9	3.0		2.92	6.4
		91.9	111.3	19.3		0.04	0.6
TR-21-068	Tranca	0.0	35.8	35.8	3.8	NS	NS
		35.8	42.4	6.6		0.01	0.2
		42.4	46.8	4.4		2.31	27.1
		46.8	61.0	14.2		0.01	0.1
TR-21-069	Tranca	0.0	102.8	102.8	3.5	NS	NS
		102.8	107.3	4.5		0.10	0.6
		107.3	111.9	4.6		1.69	2.1
		111.9	115.4	3.5		0.11	1.2
		115.4	130.1	14.7		NS	NS
TR-21-070	Tranca <i>includes</i>	0.0	39.8	39.8	5.7	NS	NS
		39.8	44.3	4.5		0.03	0.6
		44.3	46.3	2.0		0.54	4.1
		46.3	54.5	8.2		1.24	1.2
		46.3	48.3	2.0		2.30	1.9
		48.3	49.8	1.5		0.42	0.6
		49.8	54.5	4.7		1.05	1.1
		54.5	71.6	17.1		0.07	1.2
TR-21-071	Tranca <i>includes</i>	0.0	24.5	24.5	7.7	NS	NS
		24.5	41.1	16.6		0.02	1.1
		41.1	47.7	6.6		0.29	3.9
		47.7	51.8	4.0		0.53	3.7
		51.8	63.5	11.7		2.29	4.3
		51.8	53.8	2.0		1.65	3.9
		53.8	57.3	3.6		4.77	6.3
		57.3	63.5	6.2		1.07	3.2
TR-21-072	Tranca <i>includes</i>	0.0	9.3	9.3	10.2	NS	NS
		9.3	22.9	13.6		1.23	6.4
		9.3	10.9	1.6		0.30	5.2
		10.9	16.8	5.9		1.60	12.0
		16.8	20.9	4.1		0.44	1.3
		20.9	22.9	2.0		2.50	2.0
		22.9	33.9	10.9		0.05	0.8
33.9	41.2	7.3	NS	NS			
TR-21-073	Tranca	0.0	52.0	52.0	18.2	NS	NS
		52.0	58.4	6.4		0.05	1.2
		58.4	83.2	24.9		1.35	4.1

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

Drill Hole ID	Vein Structure	From (m)	To (m)	Interval (m)	ETW* (m)	Au (g/t)	Ag (g/t)
TR-21-073 <i>cont'd</i>	<i>includes</i>	58.4	63.4	5.0		1.32	7.2
		63.4	64.4	1.0		4.89	1.7
		64.4	66.8	2.5		0.40	0.6
		66.8	68.7	1.8		2.42	10.7
		68.7	70.7	2.0		0.60	1.9
		70.7	72.5	1.8		2.13	1.7
		72.5	77.2	4.8		0.43	5.3
		77.2	83.2	6.0		1.59	1.9
		83.2	96.0	12.8		0.02	0.1
TR-21-074	Tranca	0.0	12.7	12.7		NS	NS
		12.7	16.1	3.4	2.2	4.58	6.4
	<i>includes</i>	12.7	13.7	1.0		2.91	4.5
		13.7	15.1	1.4		7.70	5.7
		15.1	16.1	1.0		1.95	9.3
		16.1	49.2	33.1		NS	NS
		49.2	63.8	14.6		0.09	0.1
		63.8	84.4	20.6		NS	NS
		84.4	97.7	13.3		0.05	0.8
		97.7	103.1	5.4	3.1	4.26	4.0
		103.1	107.1	4.0		0.02	0.2
107.1	120.4	13.3		NS	NS		
TR-21-075	Tranca	0.0	68.0	68.0		NS	NS
		68.0	77.5	9.5		0.03	1.7
	<i>includes</i>	77.5	89.0	11.5	5.5	1.94	6.9
		77.5	78.5	1.0		5.00	45.2
		78.5	83.3	4.8		0.92	3.5
		83.3	86.0	2.7		3.42	3.1
		86.0	89.0	3.0		1.24	2.8
		89.0	96.0	7.0		0.25	0.8
		96.0	101.0	5.0	2.5	1.86	1.2
		101.0	106.5	5.5		0.69	2.4
		106.5	116.0	9.5		0.06	0.5
116.0	122.2	6.2	3.1	1.36	1.5		
122.2	127.6	5.5		0.11	0.8		
127.6	135.6	8.0		NS	NS		
TR-21-076	Tranca	0.0	26.4	26.4		NS	NS
		26.4	50.1	23.7		0.12	1.0
	<i>includes</i>	50.1	56.0	5.9	3.6	3.43	46.6
		50.1	50.6	0.5		3.08	100.0
		50.6	52.1	1.5		10.00	100.0
		52.1	56.0	3.8		0.92	18.3
		56.0	64.0	8.0		0.34	9.4
		64.0	71.1	7.1	4.0	2.14	10.6
		71.1	89.1	18.0		0.15	1.0
		89.1	90.1	1.0	0.6	1.17	3.0
		90.1	97.4	7.3		0.43	2.3
		97.4	102.3	4.8		0.01	0.4
		102.3	103.3	1.0	0.5	1.45	1.2
103.3	106.2	3.0		0.24	1.2		
106.2	111.3	5.1		0.00	0.0		
TR-21-077	Tranca	0.0	5.1	5.1		NS	NS
		5.1	10.1	5.0		0.10	1.0
		10.1	22.7	12.6	9.9	1.38	3.2
		22.7	25.7	3.0		0.19	0.3

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

Drill Hole ID	Vein Structure	From (m)	To (m)	Interval (m)	ETW* (m)	Au (g/t)	Ag (g/t)
TR-21-077 <i>cont'd</i>	Tranca	25.7	29.0	3.3	2.7	2.20	1.1
		29.0	37.3	8.3		0.01	0.2
		37.3	59.7	22.4		NS	NS
		59.7	63.7	4.0		0.05	0.3
		63.7	64.9	1.2	0.9	1.05	1.4
		64.9	76.2	11.4		0.00	0.1
TR-21-078	Tranca	0.0	45.0	45.0		NS	NS
		45.0	62.0	17.1		0.01	0.3
		62.0	70.9	8.9		0.59	2.9
		70.9	72.9	2.0	1.3	2.47	2.5
		72.9	75.9	3.0		0.13	0.8
		75.9	97.5	21.6		NS	NS
TR-21-079	Tranca	0.0	3.1	3.1		0.28	1.6
		3.1	18.3	15.2	11.4	3.11	3.4
	<i>includes</i>	3.1	14.1	11.1		2.23	3.3
		14.1	18.3	4.2		5.44	3.9
		18.3	47.3	29.0		0.16	0.7
		47.3	54.0	6.7	4.6	1.80	3.2
54.0	76.2	22.2		0.02	0.3		
TR-21-080	Tranca	0.0	42.8	42.8		NS	NS
		42.8	66.3	23.5		0.03	0.7
		66.3	89.9	23.5		0.24	0.5
		89.9	92.9	3.0	2.1	0.82	1.1
		92.9	97.9	5.0		0.03	0.6
		97.9	106.2	8.3	5.8	0.91	2.7
	<i>includes</i>	106.2	110.8	4.7		0.41	1.9
		110.8	112.8	2.0	1.4	5.33	352.3
		110.8	111.8	1.0		1.38	1.0
		111.8	112.8	1.0		9.50	722.0
		112.8	114.8	2.0		0.31	1.5
		114.8	125.5	10.7		0.19	1.5
TR-21-081A	Tranca	0.0	54.4	54.4		NS	NS
		54.4	57.4	3.0		0.13	0.2
		57.4	58.9	1.4		0.92	1.3
		58.9	63.9	5.0		0.04	0.2
	<i>includes</i>	63.9	75.4	11.5	6.6	4.21	4.4
		63.9	64.9	1.0		9.80	4.7
		64.9	66.9	2.0		3.59	4.8
		66.9	70.2	3.4		8.23	8.9
		70.2	75.4	5.2		0.76	1.4
75.4	89.9	14.5		0.08	0.5		
TR-21-082	Tranca	0.0	21.4	21.4		NS	NS
		21.4	28.2	6.8		0.02	1.0
		28.2	30.1	1.9	1.5	1.92	9.9
		30.1	33.5	3.4		0.01	0.5
TR-21-083	Tranca	0.0	27.1	27.1		NS	NS
		27.1	32.0	5.0		0.04	1.0
	<i>includes</i>	32.0	41.0	9.0	5.8	0.97	4.0
		32.0	34.0	2.0		1.34	8.9
		34.0	34.6	0.6		3.00	5.4
		34.6	38.0	3.4		0.38	3.2
		38.0	41.0	3.0		0.98	1.5
		41.0	48.0	7.0	4.7	0.39	0.5

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

Drill Hole ID	Vein Structure	From (m)	To (m)	Interval (m)	ETW* (m)	Au (g/t)	Ag (g/t)
TR-21-083		48.0	62.5	14.5		0.02	1.6
TR-21-084	Tranca	0.0	24.0	24.0	3.9	NS	NS
		24.0	29.0	5.0		0.10	1.0
		29.0	34.9	5.9		1.70	4.2
		34.9	38.9	4.0		0.03	0.5
		38.9	53.3	14.5		NS	NS
TR-21-085	Tranca	0.0	84.5	84.5	0.4	NS	NS
		84.5	90.0	5.5		0.01	0.2
		90.0	94.7	4.7		0.23	2.0
		94.7	95.4	0.7		1.27	3.4
		95.4	116.6	21.2		0.11	1.0
		116.6	131.1	14.5		NS	NS
TR-21-086	Tranca	0.0	7.6	7.6	10.9	NS	NS
		7.6	16.8	9.1		0.02	0.3
		16.8	93.5	76.7		NS	NS
		93.5	98.0	4.6		0.03	0.4
		98.0	112.7	14.6		0.79	3.4
		<i>includes</i> 98.0	102.6	4.6		1.14	3.4
		102.6	108.5	5.9		0.43	1.8
		108.5	112.7	4.2		0.90	5.7
		112.7	118.0	5.3		0.17	2.1
		118.0	131.1	13.1		NS	NS
TR-21-087	Tranca	0.0	49.5	49.5		NS	NS
		49.5	62.2	12.7		0.04	0.7
		62.2	77.7	15.5		NS	NS
TR-21-088	Tranca	0.0	46.6	46.6	1.0	NS	NS
		46.6	53.6	7.0		0.00	0.3
		53.6	74.8	21.2		NS	NS
		74.8	79.8	5.0		0.03	1.1
		79.8	81.8	2.0		0.32	2.1
		81.8	102.1	20.4		0.05	1.2
TR-21-089	Tranca	0.0	49.4	49.4	7.7	NS	NS
		49.4	65.2	15.9		1.09	2.5
		<i>includes</i> 49.4	53.6	4.3		0.75	0.8
		53.6	54.9	1.3		3.66	5.1
		54.9	59.9	5.0		1.15	3.1
		59.9	65.2	5.3		0.70	2.6
TR-21-090	Tranca	0.0	51.8	51.8	11.0	NS	NS
		51.8	68.8	16.9		0.08	0.5
		68.8	82.4	13.7		1.89	4.0
		<i>includes</i> 68.8	73.1	4.3		3.52	7.0
		73.1	75.4	2.4		2.01	2.1
		75.4	81.4	6.0		0.42	2.7
		81.4	82.4	1.0		3.40	2.9
TR-21-091	Tranca	0.0	20.3	20.3	4.8	NS	NS
		20.3	22.5	2.1		0.05	3.2
		22.5	30.1	7.6		0.83	8.4
		30.1	35.6	5.5		0.17	1.1
		35.6	37.1	1.5		1.74	2.5
		37.1	42.0	4.9		0.23	2.0
		42.0	47.0	5.0		1.13	5.8
		47.0	70.9	23.9		0.04	0.4

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

Drill Hole ID	Vein Structure	From (m)	To (m)	Interval (m)	ETW* (m)	Au (g/t)	Ag (g/t)
TR-21-091		70.9	100.6	29.7		NS	NS
TR-21-092	Tranca	0.0	21.5	21.5		NS	NS
		21.5	32.0	10.5		0.00	0.1
		32.0	33.5	1.5	1.2	1.65	1.4
		33.5	47.0	13.5		0.14	0.6
		47.0	53.0	6.0	4.6	0.70	1.1
		53.0	58.8	5.8		NS	NS
		58.8	69.4	10.6		0.20	0.4
		69.4	98.0	28.6		NS	NS
		98.0	102.5	4.5		0.13	0.7
		102.5	104.0	1.5	1.2	2.01	1.3
		104.0	126.5	22.5		0.03	0.4
NA-21-021	Nancite	0.0	32.8	32.8		NS	NS
		32.8	37.8	5.0		0.01	0.90
		37.8	39.8	2.0		0.63	2.06
		39.8	49.8	9.9		0.09	0.91
		49.8	51.5	1.7	1.3	0.90	4.11
		51.5	55.5	4.0		0.02	0.58
		55.5	68.6	13.1		NS	NS
NA-21-022	Nancite	0.00	44.92	44.92		NS	NS
		44.92	48.92	4.00		0.01	0.3
		48.92	51.29	2.37	1.9	4.40	7.5
		51.29	58.00	6.71		0.23	1.2
		58.00	65.53	7.53		NS	NS
NA-21-023	Nancite	0.0	29.9	29.9		NS	NS
		29.9	39.4	9.5		0.05	0.2
		39.4	47.7	8.3		0.30	0.9
		47.7	49.7	2.0	1.5	1.78	5.0
		49.7	52.2	2.5		0.13	0.7
		52.2	65.5	13.4		NS	NS
NA-21-024	Nancite	0.0	26.5	26.5		NS	NS
		26.5	28.0	1.5		0.09	0.2
		28.0	35.6	7.6		NS	NS
		35.6	41.3	5.7		0.08	0.4
		41.3	43.1	1.8	1.3	1.78	5.5
		41.3	42.0	0.7		0.66	4.5
		42.0	42.6	0.7		3.14	5.8
		42.6	43.1	0.5		1.44	6.5
				43.1	46.2	3.1	
		46.2	46.9	0.7	0.5	1.46	1.2
		46.9	54.9	8.0		0.05	1.1
		54.9	74.7	19.8		NS	NS
NA-21-025	Nancite	0.0	19.8	19.8		NS	NS
		19.8	40.1	20.3		0.03	0.2
		40.1	43.0	2.9	2.3	1.49	6.3
		43.0	49.6	6.6		0.04	1.0
		49.6	57.2	7.6		NS	NS
		57.2	58.2	1.0	0.8	0.90	0.9
		58.2	59.4	1.2		0.01	0.4
		59.4	74.7	15.2		NS	NS
NA-21-020	Nancite	0.0	51.7	51.7		NS	NS
		51.7	55.7	4.0		0.02	0.4
		55.7	58.5	2.9		0.21	3.1
		58.5	59.4	0.9	0.8	1.13	2.9

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

Drill Hole ID	Vein Structure	From (m)	To (m)	Interval (m)	ETW* (m)	Au (g/t)	Ag (g/t)	
NA-21-020 <i>cont'd</i>	Nancite	59.4	63.0	3.6	0.6	0.34	1.8	
		63.0	63.7	0.7		1.00	1.5	
		63.7	67.7	4.0		0.02	0.3	
		67.7	77.7	10.0		NS	NS	
NA-21-026	Nancite	0.0	27.5	27.5	0.4	NS	NS	
		27.5	31.5	4.0		0.19	0.2	
		31.5	32.0	0.5		1.04	0.8	
		32.0	36.2	4.2		0.40	0.7	
		36.2	38.5	2.3		2.04	7.4	
		38.5	43.4	5.0		0.05	0.8	
		43.4	44.8	1.4		3.48	4.6	
		44.8	48.8	4.0		0.07	1.2	
48.8	67.1	18.3	NS	NS				
RS-21-086	Rosario	0.0	32.1	32.1	4.9	0.03	2.4	
		32.1	36.4	4.4		0.29	39.5	
		36.4	43.4	7.0		5.14	19.9	
		<i>includes</i>	36.4	38.4		2.0	5.51	14.3
		38.4	40.7	2.3		0.41	16.4	
		40.7	43.4	2.7		8.90	27.0	
		43.4	50.6	7.2		0.12	1.0	
50.6	61.0	10.4	NS	NS				
RS-21-089	Rosario	0.0	21.2	21.2	1.0	NS	NS	
		21.2	49.4	28.3		0.02	0.2	
		49.4	50.9	1.5		2.28	1.6	
		50.9	53.9	3.0		0.39	434.3	
		53.9	56.2	2.3		1.15	17.6	
		56.2	59.6	3.4		0.31	3.8	
		59.6	79.5	19.9		0.03	0.4	
79.5	91.4	11.9	NS	NS				
RS-21-090	Rosario	0.0	19.9	19.9	0.6	NS	NS	
		19.9	35.7	15.8		0.01	0.3	
		35.7	36.5	0.8		1.16	4.5	
		36.5	42.0	5.5		0.02	0.2	
		42.0	53.1	11.1		7.8	3.13	27.0
		<i>includes</i>	42.0	46.1		4.1	1.62	6.4
		46.1	48.1	2.0		6.30	20.2	
		48.1	51.1	3.0		1.78	18.7	
		51.1	52.1	1.0		9.10	159.0	
		52.1	53.1	1.0		1.07	18.1	
53.1	72.3	19.2	0.09	1.1				
72.3	100.6	28.3	NS	NS				
RS-21-091	Rosario	0.0	45.4	45.4	9.3	0.01	0.6	
		45.4	59.4	14.1		0.26	8.7	
		59.4	67.9	8.5		0.03	0.2	
		67.9	80.8	12.8		NS	NS	
RS-21-092	Rosario	0.0	24.9	24.9	1.9	NS	NS	
		24.9	106.2	81.3		0.01	0.3	
		106.2	108.5	2.3		0.22	3.1	
		108.5	112.5	4.0		0.01	0.2	
		112.5	134.1	21.6		NS	NS	
RS-21-093	Rosario	0.0	45.7	45.7	2.1	0.01	0.4	
		45.7	105.5	59.8		0.00	0.0	
		105.5	115.3	9.8		0.07	2.0	
		115.3	118.4	3.1		1.38	12.8	

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

Drill Hole ID	Vein Structure	From (m)	To (m)	Interval (m)	ETW* (m)	Au (g/t)	Ag (g/t)
RS-21-093 <i>cont'd</i>	Rosario	118.4	121.8	3.4		0.32	1.5
		121.8	123.0	1.2	0.9	2.44	5.7
		123.0	127.0	4.0		0.26	8.6
		127.0	128.0	1.0	0.7	1.35	9.2
		128.0	131.0	3.0		0.44	20.3
		131.0	136.7	5.7		0.02	0.6
		136.7	150.9	14.2		NS	NS
RS-21-094	Rosario	0.0	23.5	23.5		NS	NS
		23.5	27.2	3.7		0.00	0.2
		27.2	98.1	70.9		NS	NS
		98.1	107.2	9.1		0.03	4.8
		107.2	108.9	1.7	1.2	1.06	6.4
		108.9	120.5	11.6		0.06	3.0
		120.5	122.1	1.6	1.1	0.18	4.8
		122.1	140.2	18.1		0.00	0.2
RS-21-095	Rosario	0.0	12.9	12.9		NS	NS
		12.9	23.5	10.6		0.04	2.6
		23.5	28.1	4.7		0.27	18.3
		28.1	30.0	1.9	1.6	4.31	23.2
		30.0	33.0	3.0		0.40	3.6
		33.0	70.1	37.1		0.02	0.5
RS-21-096	Rosario	0.0	98.3	98.3		NS	NS
		98.3	140.2	42.0		0.01	0.4
RS-21-097	Rosario	0.0	14.0	14.0		NS	NS
		14.0	96.0	82.0		0.01	0.3
RS-21-098	Rosario	0.0	28.5	28.5		NS	NS
		28.5	73.1	44.6		0.03	1.0
		73.1	94.5	21.4		NS	NS
RS-21-099	Rosario	0.0	7.7	7.7		NS	NS
		7.7	37.8	30.0		0.01	0.4
		37.8	82.2	44.5		NS	NS
		82.2	86.2	4.0		0.01	0.8
		86.2	88.2	2.0	1.4	0.92	4.6
		88.2	111.3	23.1		0.01	0.4
RS-21-100	Rosario	0.0	24.7	24.7		NS	NS
		24.7	37.7	13.0		0.06	1.6
		37.7	40.1	2.4	1.8	0.43	22.3
		40.1	61.0	20.9		0.01	0.3
RS-21-101	Rosario	0.0	58.7	58.7		NS	NS
		58.7	70.1	11.4		0.04	0.7
		70.1	74.3	4.2	3.2	0.96	10.8
		74.3	75.3	1.0		0.36	4.0
		75.3	89.6	14.3		0.02	0.3
		89.6	108.2	18.7		NS	NS
RS-21-102	Rosario	0.0	29.9	29.9		NS	NS
		29.9	34.3	4.4		0.03	1.6
		34.3	35.0	0.7	0.6	0.87	7.7
		35.0	42.6	7.6		0.12	4.6
		42.6	46.1	3.5	2.6	0.31	59.4
		46.1	80.8	34.7		0.01	0.2
RS-21-103	Rosario	0.0	12.8	12.8		NS	NS
		12.8	37.5	24.7		0.05	1.0
		37.5	41.5	4.0	3.0	2.11	22.5
		41.5	53.2	11.8		0.07	1.3

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

Drill Hole ID	Vein Structure	From (m)	To (m)	Interval (m)	ETW* (m)	Au (g/t)	Ag (g/t)
RS-21-103		53.2	70.1	16.9		NS	NS
RS-21-104	Rosario	0.0	5.7	5.7	4.8	NS	NS
		5.7	52.0	46.4		0.03	2.7
		52.0	58.9	6.9		0.18	8.1
		58.9	80.8	21.9		0.01	0.2

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

La Libertad Drill Hole Coordinates – September 8, 2021

Drill Hole ID	Vein Structure	UTM East (m)	UTM North (m)	Elevation (masl)	Total Depth (m)	Azimuth (degrees)	Dip (degrees)
TR-21-048	Tranca	705320	1354119	622	110	0	-50
TR-21-051	Tranca	705186	1354193	601	99	182	-49
TR-21-053	Tranca	705080	1354210	607	120	182	-50
TR-21-054	Tranca	705036	1354211	599	111	183	-49
TR-21-055	Tranca	704990	1354209	600	105	180	-55
TR-21-056	Tranca	706233	1354174	611	105	179	-47
TR-21-057	Tranca	706175	1354186	610	110	180	-50
TR-21-058	Tranca	705500	1354153	624	49	180	-45
TR-21-059	Tranca	705500	1354176	618	66	180	-50
TR-21-060	Tranca	706121	1354187	609	96	180	-50
TR-21-061	Tranca	706043	1354202	599	110	185	-55
TR-21-062	Tranca	704848	1354210	591	114	190	-51
TR-21-063	Tranca	705983	1354202	589	105	180	-56
TR-21-064	Tranca	705887	1354237	610	116	177	-48
TR-21-065	Tranca	704884	1354218	596	136	180	-62
TR-21-066	Tranca	705838	1354212	610	87	191	-48
TR-21-067	Tranca	704884	1354218	596	111	180	-50
TR-21-068	Tranca	705709	1354196	616	61	179	-40
TR-21-069	Tranca	704928	1354235	605	130	182	-50
TR-21-070	Tranca	705248	1354185	609	72	162	-54
TR-21-071	Tranca	705382	1354181	611	91	137	-64
TR-21-072	Tranca	705294	1354169	604	41	180	-50
TR-21-073	Tranca	704960	1354206	600	96	180	-50
TR-21-074	Tranca	705683	1354099	627	120	358	-43
TR-21-075	Tranca	704960	1354206	600	136	180	-64
TR-21-076	Tranca	705026	1354184	595	111	204	-62
TR-21-077	Tranca	705343	1354169	610	76	201	-52
TR-21-078	Tranca	705109	1354199	607	98	178	-49
TR-21-079	Tranca	705441	1354181	614	76	184	-59
TR-21-080	Tranca	705015	1354230	602	133	180	-50
TR-21-081A	Tranca	705629	1354110	640	90	350	-45
TR-21-082	Tranca	705560	1354167	626	34	180	-50
TR-21-083	Tranca	705159	1354173	597	62	180	-50
TR-21-084	Tranca	705620	1354130	639	53	0	-40
TR-21-085	Tranca	705185	1354221	607	131	180	-50
TR-21-086	Tranca	705256	1354232	609	131	180	-50
TR-21-087	Tranca	705560	1354190	623	78	180	-50
TR-21-088	Tranca	705560	1354191	623	102	180	-70
TR-21-089	Tranca	705441	1354115	634	123	359	-50
TR-21-090	Tranca	704753	1354185	567	94	184	-45
TR-21-091	Tranca	704662	1354093	561	101	10	-46
TR-21-092	Tranca	704584	1354166	554	126	180	-50
NA-21-020	Nancite	704677	1353922	576	78	167	-45

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

Drill Hole ID	Vein Structure	UTM East (m)	UTM North (m)	Elevation (masl)	Total Depth (m)	Azimuth (degrees)	Dip (degrees)
NA-21-021	Nancite	704641	1353906	582	69	174	-51
NA-21-022	Nancite	704555	1353882	587	66	177	-58
NA-21-023	Nancite	704515	1353871	585	66	165	-61
NA-21-024	Nancite	704471	1353863	584	75	171	-50
NA-21-025	Nancite	704417	1353846	584	75	163	-50
NA-21-026	Nancite	704370	1353831	583	67	174	-50
RS-21-086	Rosario	691295	1349718	572	61	151	-51
RS-21-089	Rosario	691184	1349677	553	91	157	-50
RS-21-090	Rosario	691162	1349659	541	101	166	-50
RS-21-091	Rosario	691553	1349845	578	81	158	-50
RS-21-092	Rosario	691274	1349772	551	134	157	-50
RS-21-093	Rosario	691218	1349751	540	151	157	-50
RS-21-094	Rosario	691118	1349683	537	140	158	-52
RS-21-095	Rosario	691138	1349633	535	70	157	-45
RS-21-096	Rosario	691104	1349670	531	140	168	-50
RS-21-097	Rosario	691100	1349635	528	96	152	-52
RS-21-098	Rosario	691133	1349628	535	94	202	-45
RS-21-099	Rosario	691073	1349631	533	111	157	-52
RS-21-100	Rosario	691082	1349599	544	61	149	-45
RS-21-101	Rosario	691056	1349607	542	108	163	-47
RS-21-102	Rosario	691061	1349584	551	81	157	-50
RS-21-103	Rosario	691024	1349557	565	70	150	-45
RS-21-104	Rosario	690995	1349541	562	81	155	-50

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.