

**CALIBRE REPORTS EXPLORATION DRILL RESULTS FROM THE PAN MINE IN NEVADA
INITIAL DRILL RESULTS DEMONSTRATE RESOURCE EXPANSION AND HIGHER GRADE POTENTIAL**

Calibre Mining News Release, March 8, 2022 Drill Hole Table *see notes at the bottom of the table

Hole	From (ft)	To (ft)	Length (ft)	Grade (g/t Au)	Grade (opt Au)	From (m)	To (m)	Length (m)
PC21-001	No Significant Results							
PCM21-001	149.5	261	111.5	0.833	0.024	45.57	79.55	33.99
includes	159.5	178	18.5	1.371	0.040	48.62	54.25	5.64
includes	204	217	13	1.646	0.048	62.18	66.14	3.96
and	292	365	73	0.376	0.011	89.00	111.25	22.25
and	452	476	24	0.356	0.010	137.77	145.08	7.32
and	499	567	68	0.354	0.010	152.10	172.82	20.73
PR21-001	255	440	185	0.455	0.013	77.72	134.11	56.39
and	455	660	205	0.403	0.012	138.69	201.17	62.48
includes	550	565	15	1.029	0.030	167.64	172.21	4.57
PR21-002	225	235	10	0.418	0.012	68.58	71.63	3.05
and	260	405	145	0.437	0.013	79.25	123.45	44.20
PR21-003	505	520	15	0.388	0.011	153.93	158.50	4.57
and	605	620	15	0.438	0.013	184.41	188.98	4.57
PR21-004	No Significant Results							
PR21-005	No Significant Results							
PR21-006	No Significant Results							
PR21-007	No Significant Results							
PR21-008	No Significant Results							
PR21-009	No Significant Results							
PR21-010	No Significant Results							
PR21-011	No Significant Results							
PR21-012	No Significant Results							
PR21-013	No Significant Results							
PR21-014	25	40	15	0.649	0.019	7.62	12.19	4.57
PR21-015	No Significant Results							
PR21-016	65	75	10	0.320	0.009	19.81	22.86	3.05
PR21-017	60	90	30	0.649	0.019	18.29	27.43	9.14
PR21-018	No Significant Results							
PR21-019	No Significant Results							
PR21-020	20	30	10	0.378	0.011	6.10	9.14	3.05
and	45	85	40	0.373	0.011	13.72	25.91	12.19
and	445	455	10	0.336	0.010	135.64	138.68	3.05
PR21-021	0	100	100	0.400	0.012	0.00	30.48	30.48
and	205	215	10	0.223	0.007	62.48	65.53	3.05
and	275	330	55	0.423	0.012	83.82	100.58	16.76
PR21-022	0	40	40	0.321	0.009	0.00	12.19	12.19
and	70	205	135	0.582	0.017	21.34	62.48	41.15
includes	175	185	10	1.758	0.051	53.34	56.39	3.05
and	245	260	15	0.242	0.007	74.68	79.25	4.57
and	270	350	80	0.676	0.020	82.30	106.68	24.38

includes	310	320	10	1.065	0.031	94.49	97.54	3.05
PR21-023	No Significant Results							
PR21-024	No Significant Results							
PR21-025	10	40	30	0.413	0.012	3.05	12.19	9.14
PR21-026	No Significant Results							
PR21-027	0	25	25	0.292	0.009	0	7.62	7.62
and	65	80	15	1.076	0.031	20	24.38	4.57
PR21-029	No Significant Results							
PR21-030	No Significant Results							
PR21-043	95	115	20	0.360	0.011	28.96	35.05	6.10
PR21-044	235	385	150	0.473	0.014	71.63	117.35	45.72
and	635	675	40	0.294	0.009	193.55	205.74	12.19
PR21-045	200	365	165	1.024	0.030	60.96	111.25	50.29
includes	205	225	20	3.889	0.113	62.48	68.58	6.10
includes	325	335	10	1.470	0.043	99.06	102.11	3.05
and	445	490	45	0.368	0.011	135.64	149.35	13.72
PR21-046	75	105	30	0.322	0.009	22.86	32.00	9.14
and	215	230	15	0.462	0.013	65.53	70.10	4.57
PR21-048	5	55	50	0.357	0.010	1.52	16.76	15.24
and	95	140	45	0.596	0.017	28.96	42.67	13.72
PR21-049	No Significant Results							
PR21-050	80	100	20	0.521	0.015	24.38	30.48	6.10
PR21-054	65	85	20	0.327	0.010	19.81	25.91	6.10
PR21-056	40	95	55	0.551	0.016	12.19	28.96	16.76
includes	50	60	10	1.165	0.034	15.24	18.29	3.05
and	110	130	20	0.291	0.008	33.53	39.62	6.10
and	140	170	30	0.232	0.007	42.67	51.82	9.14
and	210	235	25	0.375	0.011	64.01	71.63	7.62
PR21-059	No Significant Results							
PR21-061	No Significant Results							
PR21-063	No Significant Results							

Notes: All holes were drilled at angles of -45 to -90 degrees at azimuths designed to intersect targeted structures as nearly as possible to perpendicular when possible. Some drill holes and intercepts reported on here did not cross mineralization perpendicularly, and do not represent exact 'true widths'. These instances are illustrated in the sections provided. The Company conducts a significant QA/QC program which includes the insertion of assay standards, blanks, and duplicates in the sample stream to ensure the assay lab results are within specified performance levels. Down hole deviation surveys are provided by International Directional Services, utilizing a surface recording gyroscope, and by trained drill crews operating a north seeking gyroscope supplied by REFLEX.